

DATASHEET

TYPE HSGM STYRO-CUT 230

The powerful performance professional tool for the Building Trade
With electronic power control,
for an optimal adjustment of the blade temperature.
 For board thicknesses **up to 230mm (9.1")** and for specialty cuts.

Technical Description:

Heats up in only 10 seconds
 Supply voltage: 230V-50Hz
 Power input: max. **230 Watt**
Optimal level of efficiency
 LED-power indicator
 Protective insulation
 Mains cord 3m
 Blade temperature 500°C (930°F) max.
 Eliminates styrofoam dust
 Low Weight: 0,6 kg, 1,5 kg incl. plastic case and accessories



Basic Kit:

- 1 STYRO-CUT 230
- 2 Blades (1x DSS-220 for boards up to 200 mm and 1x DSS-250 for boards up to 230mm)
- 1 Brass brush
- 1 Screwdriver
- 1 Manual
- 1 Solid plastic case

Practicable blades:

Type DSS-200
 For boards
 up to 180 mm (7.1")




Type DSS-220
 For boards
 up to 200 mm (7.9")




Type DSS-250
 For boards
 up to 230 mm (9.1")




Type C-100
 For boards
 up to 100 mm (4")




Type C-140
 For boards
 up to 140 mm (5.5")



Type C-160
 For boards
 up to 160 mm (6.3")



Type C-180
 For boards
 up to 180 mm (7.1")




Type C-200
 For boards
 up to 200 mm (7.9")




Type C-230
 For boards
 up to 230 mm (9.1")



Type CN-14, curved
 For 14 mm grooves



Type CN-20 curved
 For 20 mm grooves




Type CN-26 curved
 For 26 mm grooves



Type CR-20 curved
 For 20 mm grooves
 With depth guide



Type CS-20 curved
 For 20 mm grooves
 With depth guide



Connector socket cutter
 Typ D68-61
 For cutting holes Ø 68 mm

